


REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 2/25/97		3. REPORT TYPE AND DATES COVERED Final 30 Sep 1992 - 30 Sep 1996
4. TITLE AND SUBTITLE Statistical Inversion of Seismic and Heat Flow Data			5. FUNDING NUMBERS PE 61102F Proj 2309/AS F49620-92-J-0544	
6. AUTHOR(S) Raymond Jeanloz				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Dept of Geology & Geophysics University of California, Berkeley 301 McCone Hall Berkeley CA 94720			AFOSR-TR-97 	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) AFOSR/NM 110 Duncan Ave Bolling AFB DC 20332			10. SPONSORING/MONITORING AGENCY REPORT NUMBER Monograph Series of Seismic Research #97-09	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT APPROVED FOR PUBLIC RELEASE DISTRIBUTION UNLIMITED			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Novel methods of characterizing heterogeneity inside the earth have been developed based on the theoretical study of wave propagation through complex media. Multiply scattered waveforms, for example from the "coda" regions of seismic records, can be used to characterize statistical properties of the heterogeneity. The approach used can accommodate strong multiple scattering, such that one is enabled to investigate the conditions under which the heterogeneity is so important that effectively no energy is transmitted forward by the seismic waves. Similar theoretical methods can be utilized to investigate diffusive processes through heterogeneous media, such as heat flow through the earth's crust. The seismological application is being tested on detailed measurements obtained from the KTB (the German very deep) borehole, with initial results appearing to be most promising.				
DTIC QUALITY INSPECTED 2				
14. SUBJECT TERMS Seismology Seismic wave propagation Heat flow			15. NUMBER OF PAGES 9	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED		18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED		19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED
				20. LIMITATION OF ABSTRACT SAR

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to *stay within the lines* to meet *optical scanning requirements*.

Block 1. Agency Use Only (Leave blank).

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in.... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement.

Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - Leave blank.

DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract. Include a brief (*Maximum 200 words*) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (*NTIS only*).

Blocks 17. - 19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

FINAL TECHNICAL REPORT
GRANT # F49620-92-J-0544

STATISTICAL INVERSION OF SEISMIC AND HEAT FLOW DATA

PRINCIPAL INVESTIGATOR PROF. RAYMOND JEANLOZ

The contract supported a multi-disciplinary research effort among geophysicists and theoretical physicists to evaluate new methods of characterizing heterogeneity of material properties inside the Earth. Most of the effort involved developing new theoretical techniques of using seismological and other geophysical observations to characterize the statistical variations of physical properties with location in the Earth. Rather than focussing on the forward problem of determining, for example, how heterogeneities in elastic-wave velocities causes scattering of seismic waves, the approach highlighted the use of inverse methods to investigate the amplitudes (waveforms) of multiply scattered waves.

The general approaches used are described in P. Sheng's monograph "Introduction to Wave Scattering, Localization and Mesoscopic Phenomena", which was written based in part on the work supported by this contract. The methodology can account for arbitrarily strong multiple scattering, such that one can investigate the conditions under which localization becomes significant; that is, the conditions under which the scattering is so strong that effectively no wave energy is propagated forward any more. This is an important consideration because it allows one to estimate the conditions under which information is fundamentally lost from the seismogram, for example.

The new applications have required further development of the theory, which has been pursued using diagram methods of field theory. Follow-up work has included developing software to implement the theory and to analyze actual data. An emphasis has been placed on modelling data from the German KTB hole, because this is the best documented deep coring of the Earth's crust available for study. Although application of the theory to inverting seismic waveforms from the KTB hole is straightforward in principle, data handling has been trickier -- hence much slower -- than anticipated because of technical difficulties including identifying and removing unreliable data (a problem that has plagued virtually all analyses of data from this borehole). The first round of analysis is nearing completion, and a major publication is in preparation by Z. Zhang and P. Sheng on the results of this work.

PUBLICATIONS

P. Sheng, "Introduction to Wave Scattering, Localization and Mesoscopic Phenomena" (Academic Press, San Diego : c1995).

Z. Zhang and P. Sheng, manuscript in preparation (1997)

19970604 148

Final Technical Report

AFOSR Grant 92-J-0544

R. Jeanloz
University of California, Berkeley

The grant supported an interdisciplinary research effort among physicists and geophysicists to develop new ways of characterizing the heterogeneity of the Earth's interior. The motivation for this work comes from the increasing recognition that geophysical observations, notably from seismology, can be significantly influenced by the presence of locally strong heterogeneities within the planet. For example, scattering appears to play a key role in the development of the seismic Lg phase, and the classical "Conrad Discontinuity" is widely attributed to varying degrees of quasi-coherent scattering rather than to the occurrence of a true structural or lithological boundary at mid-crustal depths. Strong scattering of seismic waves is also likely to take place due to the presence of heterogeneities deep in the mantle.

Our approach has been twofold: i) the use of forward modelling applied to field observations in order to characterize the nature of heterogeneities in the Earth's crust; and ii) the development of inverse methods to extract information about heterogeneities and underlying (larger-scale) structures from seismological and other geophysical observations. As we are considering potentially strong heterogeneities that can give rise to complex multiple scattering phenomena, we apply formalisms that have been successfully developed for such problems in other research disciplines [1].

1) Characterization of Crustal Heterogeneity

The main difficulty in characterizing the spatial heterogeneity in the physical properties of the Earth's interior is to obtain an adequate sampling over distance scales that are sufficiently large to be useful. To this end, we have analyzed the density and seismic-wave velocity logs obtained from the KTB deep borehole in Germany. The data provide the longest sequence of high-quality petrophysical measurements now available, representing an essentially continuous sampling over a depth interval of nearly 6 km into the crust (Fig. 1). Also, the KTB borehole transects deformed metamorphic units typical of mid- to lower-continental crust, and is therefore highly relevant for obtaining a picture of large-scale heterogeneity underlying many seismic stations around the world.

The autocorrelation of the density (ρ), longitudinal velocity (V_p) and transverse velocity (V_s) logs with depth (z) can each be fitted with exponential functions, $\exp(-\Delta z/d)$ where Δz is the depth lag and d is a decay (decorrelation) length. The resulting values of d , 5.3 m for the density and 2.2 m for both velocities, is in good accord with what has been independently found for the KTB logs.

It is remarkable that similar decay lengths of the order of meters are obtained from entirely different rock sequences [2]: records sampled in different parts of the world and representing completely different lithologies (for example, from "layer-cake" sedimentary sequences as opposed to the high-grade metamorphic units of the KTB borehole). Why such a wide variety of crustal rock distributions tend to exhibit similar decorrelation lengths is a basic question that remains unanswered; it appears to be related to the "memory" inferred from Markov analyses of stratigraphic sequences, which has yet to be satisfactorily

explained after years of study [e.g., 3]. Indeed, our study reveals new aspects of the stratigraphic "memory" effect that can help to explain this phenomenon.

In order to translate what the detailed KTB logging measurements of heterogeneity imply for seismic records, we have extended a theoretical analysis that has been successfully developed for characterizing the scattering of scalar and electromagnetic waves [4]. Specifically, we wish to quantify the scattering of seismic waves by the heterogeneities in velocities and density (or impedances), even if over distances *larger* than the sample lengths obtained from the KTB borehole.

To begin, we focus on a single parameter, the localization length ξ_c which provides a measure of the distances over which strong scattering becomes dominant. In one dimension, the localization length for seismic waves can be thought of as the distance over which backscattering has effectively blocked any forward transmission of elastic energy. In two and three dimensions, it provides a distance scale within which strong (multiple) scattering characterizes the seismic-wave propagation [cf. 5].

For a given propagation distance, L , the transfer-matrix method can be used to calculate the transmission spectrum $T(\omega)$ as a function of frequency (ω) from the density and velocity logs, thereby yielding estimates of the frequency-dependent localization length $\xi(\omega)$ [4]. Specifically, when L is on the order of $\xi(\omega)$ for an infinite medium, $T(\omega)$ exhibits resonant-like behavior; near the resonance frequency, ω_r , $T(\omega)$ takes on a Lorentzian shape with half-width $\Delta\omega_r$. Associating the dwell time $\Delta\omega_r^{-1}$ with a diffusion time for energy transport ultimately yields the localization length

$$\xi(\omega_r) = a \Delta\omega_r L^2 v^{-1} \quad (1)$$

where $a \approx 1.5$ is a constant [4]. In (1), v is the effective medium wave speed given by

$$v^{-2} = \langle \rho(z)/M(z) \rangle \quad (2)$$

where M is either the longitudinal or shear modulus for, respectively, P and S waves, and the brackets indicate an average over depth, z .

The localization length at each resonant mode of the transmission spectrum is numerically calculated as an average over a small frequency interval, with the results for the V_P and V_S logs of the KTB borehole being shown in Figs. 2 and 3. As frequencies approach the typical seismic band it is clear (for the S waves in particular) that values of ξ reach 10-20 km, which is well in excess of the length of the original velocity log. The important point here is that a method has been developed to accurately calculate the localization length from a single finite-length configuration; this is equivalent to accurately evaluating the multiple scattering loss from a single configuration. Hilbert transformation yields the fluctuations of wave velocities as a function of frequency from the localization-length spectra [4].

Thus, it is possible to obtain quantitative data about the effects of heterogeneities over distance scales approaching those relevant to problems in seismic-wave propagation through the crust and mantle. It is evident based on direct logging measurements that strong (multiple) scattering can have a significant influence over distances of tens of km, and therefore cannot be ignored in general. It is worth noting, in this regard, that the original velocity and density logs do not exhibit particularly large or anomalous fluctuations with depth (Fig. 1). Therefore, we expect that scattering effects due to heterogeneities in physical properties can be locally much stronger within the Earth's crust or mantle than we have inferred from the more "typical" variations evident from the KTB well logs.

2) *Inverse Modelling of Strongly Scattered Seismic Waveforms*

We examine strong scattering (e.g., at high-frequencies) as a model problem in order to determine how much information can be extracted from a seismic waveform representing transmission through a very heterogeneous medium. The underlying analysis stems from inversion methods described elsewhere, specifically using White's "W Equation" [e.g., 6, 7].

To give a flavor of what can be done, we consider a medium having a smooth, large-scale velocity variation of 0.5 (Fig. 4) on which is superimposed a random small-scale heterogeneity having a variance of 0.3 (Fig. 5); all units are non-dimensionalized in this analysis. The degree of heterogeneity is considerably larger than is the case with the KTB data, and its effect on seismic waveforms is illustrated by evaluating the propagation of a Gaussian pulse through both the smooth and heterogeneous model media (Fig. 6). This case actually provides a conservative view, in that a Ricker pulse (for example) exhibits roughly 3 orders of magnitude greater effect of scattering on the amplitudes due to the presence of higher-frequency components in the underlying waveform than is the case with the Gaussian pulse.

The inversion involves applying a layer-peeling algorithm in order to extract the large-scale velocity structure that is essentially buried in the signal due to the effects of multiple scattering. By necessity, the small-scale heterogeneities are modelled assuming a Gaussian spectrum. From analyses of real rock sequences, as described above, there is reason to suspect this assumption. Further studies of actual rock sequences, as well as of recordings of seismic waves after propagation through strongly heterogeneous regions of the Earth, will be required in order to go beyond this assumption.

An example of how well the inversion scheme works is illustrated in Fig. 7, which summarizes results assuming mismatched (A) and pressure-release (B) boundary conditions as compared to the actual model variation of velocity (C) (again, results are shown in non-dimensional form, plotted here with a change of axis). It is evident that the case assuming mismatched boundary conditions yields a better inversion than the pressure-release case. The reason for this difference has to do with the treatment of higher frequencies in the latter case.

Although the model of heterogeneity examined here is admittedly idealized, it is worth noting that the magnitude of the velocity fluctuations is much greater than is normally considered in seismology. Thus, although the inversion scheme is still at a rudimentary stage, it clearly shows the potential for extracting information about large-scale structure even from waveforms that appear to be dominated by "noise" due to multiple scattering caused by significant small-scale heterogeneities.

3) *Analyses of Non-seismological Data*

We have initiated studies of three other types of geophysical measurements that may complement seismological determinations of structural heterogeneity within the Earth. First, we have been pursuing both forward and inverse models of electromagnetic propagation into the crust. The objective is to make a link between traditional finite-element methods, which describe the crustal structure in terms of homogeneous blocks, and the scattering approach explored above [e.g., 1, 4]. The motivation for this work is that considerable information is available from electromagnetic studies of shallow crustal structures. Moreover, because of the wide frequency range that is sampled (typically ≥ 2 -3 orders of magnitude wider than the seismic data), there is a possibility of obtaining a better characterization of the spectrum of localization lengths.

Second, because the scattering approach can be applied to diffusive processes as well as wave propagation [1], we have been examining the use of heat-flow measurements as an added constraint on the nature of large-scale heterogeneities in rock types throughout

the crust. It is well known that regional heat flow measurements can be interpreted in terms of heterogeneities in thermal properties (either or both heat production and thermal diffusivity) throughout the crust [e.g., 8]. Although the analysis is in progress, it appears quite possible to extend previous analyses, which have necessarily assumed weak scattering, to more realistic conditions of strong heterogeneity. The advantage over seismic observations is that there tends to be an averaging over the smallest spatial scales, such that one has a hope of getting a clearer picture of the intermediate scale of heterogeneity in structure.

Finally, we have explored the potential application of an entirely novel method of geophysical observation, neutrino absorption spectroscopy which in the future may provide independent constraints on the Earth's internal structure [9]. Motivated by the current development of "observatories" (detector arrays) intended to record high-energy (\sim TeV-PeV) neutrinos from astrophysical sources, we have developed methods of imaging large-scale features of Earth structure that complement seismological methods. In particular, neutrino absorption depends on density (average nucleon number) with a spatial resolution and precision that should be comparable to the seismological constraints (i.e., from normal modes). Furthermore, the energy dependence of neutrino absorption can potentially be used to obtain compositional information about the Earth's interior (variations in mean atomic weight), thereby significantly enhancing current means of interpreting seismological observations. As the detector arrays are only beginning to become operational, our study anticipates a new method of geophysical imaging that is could become important in the coming decade or two.

4) Summary

Our investigations of heterogeneity inside the Earth depart from the traditional methods of geophysical imaging, which assume that the planetary interior can be described as an aggregate of homogeneous volumes. Instead, we focus on the intrinsic spatial variability of material properties inside the Earth, allowing for the possibility of strong heterogeneity causing multiple scattering and related phenomena such as wave localization. The objective is both to characterize the real (heterogeneous) structure of the Earth and to understand the causes of wave arrivals and other phenomena not anticipated from the classical deterministic models of the interior: e.g., refractions caused by variations in correlation lengths or other measures of heterogeneity, rather than actual lithological structure. Analyses of geophysical observations from the KTB borehole and elsewhere demonstrate that heterogeneity is realistically significant enough that it cannot be ignored. The theoretical foundation required to treat these effects is developed, with extensions to higher dimensions (1- and 2-D to 3-D) and from scalar- to vector-wave equations (e.g., including conversions) having been derived in principle.

Further applications are promising. The most important avenues to pursue include carrying out additional studies of detailed geophysical observations comparable to those of the KTB borehole described above. Anisotropies in localization length must be considered, as must alternative means of quantifying the heterogeneity. It is only in this way that the true structural heterogeneity of the interior can be characterized, as there is little point in devising models of the Earth's heterogeneity unless they agree with observations. Additional theoretical work is required to enhance the inversion approaches described above: make them less dependent on simplifying approximations, as noted above, and test them rigorously against real data. It is also necessary to identify the more global or qualitative phenomena induced by heterogeneity that could be recognized in seismological and other geophysical observations. For this reason, further attempts at simultaneously analyzing (or inverting) several types of geophysical data sets from one area (e.g., seismological, electromagnetic, etc.) appear to be especially promising.

- [1] P. Sheng, *Introduction to Wave Scattering, Localization, and Mesoscopic Phenomena* (Academic Press, New York, 1995).
- [2] B. White, P. Sheng and B. Nair, *Geophysics*, 55, 1158 (1990).
- [3] J. Ferguson, *Mathematics in Geology* (Allen & Unwin, London, 1988).
- [4] Z. Q. Zhang, K. C. Chiu and D. Zhang, *Phys. Rev. B*, 54, 11891 (1996).
- [5] P. Sheng and Z. Q. Zhang, *Phys. Rev. Lett.*, 74, 1343 (1995).
- [6] G. Papanicolaou, M. Postel, P. Sheng and B. White, *Wave Motion*, 12, 527 (1990).
- [7] M. Asch, W. Kohler, G. Papanicolaou, M. Postel and B. White, *SIAM Rev.*, 33, 519 (1991).
- [8] K. P. Furlong and D. S. Chapman, *Geophys. Res. Lett.*, 14, 314 (1987).
- [9] C. Kuo, H. J. Crawford, R. Jeanloz, B. Romanowicz, G. Shapiro and M. L. Stevenson, *Earth Planet. Sci. Lett.*, 133, 95 (1995).

FIGURE CAPTIONS

- Fig. 1 P- and S-wave velocity logs as a function of depth, $V_P(z)$ and $V_S(z)$ in km/s, for the KTB deep borehole in Germany.
- Fig. 2 P-wave localization length as a function of frequency, $\xi_c(\omega)$ in m, obtained from the KTB deep borehole logs (Fig. 1).
- Fig. 3 S-wave localization length as a function of frequency, $\xi_c(\omega)$ in m, obtained from the KTB deep borehole logs (Fig. 1).
- Fig. 4 Large-scale (smooth) variation in wave velocity as a function of depth, $\langle c(z) \rangle$ in nondimensional units, assumed for the inversion model problem.
- Fig. 5 Variation in wave velocity as a function of depth, $c(z)$ in nondimensional units, assumed for the inversion model problem. The wave velocity is given by a short-scale variance of 0.3 superimposed on the large-scale structure of Fig. 4.
- Fig. 6 Wave amplitude as a function of time, $w(\tau)$ in nondimensional units, assuming a Gaussian pulse that has been propagated through the smooth structure of Fig. 4 (heavy curve) and through the heterogeneous structure of Fig. 5 (crosses and thin curve).
- Fig. 7 Smooth velocity anomaly, $\Delta \langle c(z) \rangle$ in nondimensional units, recovered from a Ricker pulse that has been propagated through the heterogeneous structure (Fig. 5) assuming either mismatched (A) or pressure-release (B) boundary conditions. For comparison, the actual structure is given by curve C.




Fig. 1




Fig. 2




Fig. 3

